




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : B01D 15/08, G01N 30/60	A1	(11) International Publication Number: WO 00/00259 (43) International Publication Date: 6 January 2000 (06.01.00)
(21) International Application Number: PCT/GB99/01284 (22) International Filing Date: 26 April 1999 (26.04.99) (30) Priority Data: 9814195.5 30 June 1998 (30.06.98) GB (71) Applicant (for all designated States except US): MILLIPORE CORPORATION [US/US]; 80 Ashby Road, Bedford, MA 01730-9125 (US). (72) Inventor; and (75) Inventor/Applicant (for US only): FRAZER, Neil, Francis [GB/GB]; Parkhill Cottage, Cow Lane, South Woodchester, Stroud, Gloucestershire GL5 5HN (GB). (74) Agents: GREENWOOD, John, David et al.; Graham Watt & Co., Riverhead, Sevenoaks, Kent TN13 2BN (GB).		(81) Designated States: JP, US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report.</i>

(54) Title: CHROMATOGRAPHIC COLUMN**(57) Abstract**

A chromatography column (40) in which an adjustable cell assembly (50) is movable within a housing (44) by a support assembly including three ball-threaded rods (66) interlinking the adjustable cell assembly (50) and housing (44). Each rod (66) is rotatable but longitudinally fixed in a base plate (64) fixed to the adjustable cell assembly (50). A ball nut (78) is mounted on each rod (66) and fixed to a flange (60) fixed to the housing (44). Fixed to each rod (64) is a spur gear (70), all the gears (70) being interconnected by a ring gear (80). A handwheel fixed to one rod (66) allows manual adjustment of all the rods (66) simultaneously to provide rapid adjustment of the position of the adjustable cell assembly (50) relative to the housing (44).



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

CHROMATOGRAPHY COLUMN

The present invention relates to a chromatography column.

Frequently it is desirable to separate out one or more useful components from a fluid mixture that contains other components which may not be useful or are less valuable. To accomplish this it is often necessary or desirable to fractionate such a fluid mixture to separate out the useful or desired components. This can be carried out by using liquid chromatography systems. Liquid chromatography may briefly be described as the fractionation of components of a mixture based on differences in the physical or chemical characteristics of the components. The various liquid chromatographic systems fractionate the components with a fractionation matrix. Some liquid chromatographic matrix systems fractionate the components of a mixture based upon such physical parameters as molecular weight. Still other liquid chromatographic systems will fractionate the components of a mixture based upon such chemical criteria as ionic charge, hydrophobicity, and the presence of certain chemical moieties such as antigenic determinants or lectin-binding sites on the components.

Chromatography systems of various sized are used in both laboratory analysis operations and for industrial

scale production operations in which separation steps such as separating out a fraction from human blood or separating out impurities from a pharmaceutical can be carried out on a large scale in a batch process.

A typical known construction of chromatography column is shown in Figure 1 in which a column tube 2 for holding a chromatography medium is defined laterally by a cylindrical housing 4, a fixed cell assembly 6 fixed at one end of the cylindrical housing 4 (in this case the lower end of the housing 4) and an adjustable cell assembly 8 towards the other end of the housing 4 (in this case the upper end of the housing 4). Upper and lower valve assembly 10 and 12 provide access to the column tube 2 from outside the column tube 2.

The adjustable cell assembly 6 is relatively movable within, and sealable to, the cylindrical housing 4. It is held in place beneath a support plate 14 by a number of threaded rods 16, which plate 14 is in turn, supported by a flange 18 on the housing 4 by a number of rods 20 between the plate 14 and flange 18. Each rod 18 is fixed to the support plate 14 but passes through a respective through-hole in the flange 18 and fixed relative to it by a pair of bolts 22, 24 mounted on each rod above and below the flange 18.

Adjustments of the position of the adjustable cell

assembly 6 within the housing 4 is a very time consuming process. If the adjustable cell assembly 8 is to be moved upwards, the nut 22 of one rod must be loosened, by a quarter turn say, and the nut 24 moved upwards by that amount. This is repeated until all the nut positions on the rods 20 have been adjusted by the same small amount. The sequence is then repeated, possibly many times, until the adjustable cell assembly 8 is in the desired new position.

Similarly if the adjustable cell assembly is to be forced downwards, to compact a chromatography medium in the column tube for example, the lower nut 24 on rod is loosened by a quarter turn and upper nut 22 tightened downwards to force the adjustable cell assembly downwards. When all the nuts 22, 24 on the rods 20 have been so adjusted the sequence is repeated until the adjustable cell assembly 6 exerts the required pressure on the chromatography medium.

The adjustment of the position of such adjustable cell assemblies is very time consuming, especially with large industrial columns, and the resultant down-time results is lost productivity as the column is idle while it is being adjusted.

The present invention, which is as claimed in the claims, provides a chromatography column which is more

readily adjustable than such prior art chromatography columns.

An embodiment of the present invention will now be described, by way of example only, with reference to the accompanying drawings, of which:

Figure 1 is a side sectional view of a prior art chromatography column;

Figure 2 is a side sectional view of a chromatography column according to the present invention;

Figure 3 is a detailed side sectional view of a part of the chromatography column of Figure 2; and

Figure 4 is an end view of Figure 3 viewed in the direction IV of Figure 3.

Referring to Figure 2, a chromatography column 40 includes a column tube 42 partially defined by a cylindrical housing 44 with an outwardly extending flange 46 at its lower end to which is bolted, in sealing relationship, a fixed cell assembly 48. The upper end of the column tube 42 is defined by an adjustable cell assembly 50 mounted for movement relative to the housing 44.

The housing 44 is, in this case, mounted on a pair of I-beams 52 by bolts 54 joining the I-beams to an annular collar 56 fixed to surrounding the housing 44.

Access to the interior of the column tube is provided

by upper and lower valve assemblies 60 and 58. The specific arrangements of these valve assemblies and associated controls are not part of the present invention. They may be any suitable system for the processes to be carried out by the chromatography column 40 and so will not be described in any further detail.

Referring now also to Figures 3 and 4, the housing 44 has at its upper extremity an outwardly extending annular flange 60. The adjustable cell assembly 50 is secured to an annular plate 62. The flange 60 and plate 62 have a series of three, circumferentially spaced apart aligned bores, such as 64, for receiving a respective threaded support rod 66 (one of which is fully shown in Figures 2 and 3).

Each rod 64 is rotatable but fixed longitudinally with respect to the plate 62 by a flange mounted bearing 68 and a keyed spur gear 70. A handwheel 72 is fixed to the upper end of one rod 66 so the rod 66 can be rotated manually.

Each rod 66 is located in a bore 64 of the flange 60 by a retaining housing 74 secured to the flange 60 by a clamp nut 76. A ball nut assembly 78 is located on each rod 66 above the retaining housing 74 and secured to the housing 44 as shown in Figure 2.

An annular ring gear 80 is mounted for rotation on the base plate 62 within a two-part annular mounting 82

comprising a lower ring with an L-shaped cross-section 84 and an annular top-plate 86.

The ring 84 and top-plate 86 are secured together to hold the ring gear 80 in place, and to the base plate 62, by a number of bolts 88. The ring gear 80 engages each of the spur gears 70 keyed to respective rods 66 which rods 66 are therefore all constrained to rotate together and so be simultaneously adjusted on manual rotation of the handwheel 72. A non-rotatable locking cog (not shown) is movable into and onto of engagement with one of the spur gears 70 locks one rod 66 against rotation, and so all of the rods 66, when the adjustable cell assembly 50 has been moved to the desired position within the housing 44.

The rods 66 may be sufficiently long to allow the adjustable cell assembly 50 to be fully retracted from within the portion of the housing 44 used to define the column tube 42 to allow full access to the interior of the housing 44 by an operator.

The diameter of the handwheel 72 is chosen to allow manual application of the maximum pressure to be applied to compress the chromatography column medium to the required degree.

The support assembly of the embodiment of Figures 2 to 4 provides a compact and efficient means of providing simultaneous adjustment of the adjustable supports (rods

66) mounting the adjustable cell assembly 50 to the housing 44 but other designs of support assemblies may be employed to put the present invention into effect. The drive means for adjusting the adjustable supports may be an electric motor, for example, which would allow a degree of automation to the adjustment of the position of the adjustable cell assembly 50.

CLAIMS:

1. A chromatography column including a column tube for holding a chromatography medium defined in part by a housing and an adjustable cell assembly movable relative to and within the housing, the adjustable cell assembly being mounted on the housing and movable relative to it by a support assembly which includes a plurality of adjustable supports, the adjustable supports being interconnected such that they are adjustable simultaneously and a drive means for effecting the simultaneous adjustment of the adjustable supports.

2. A chromatography column as claimed in claim 1 in which each adjustable support comprises a ball screw assembly which includes a rotatable, ball-threaded rod which is longitudinally fixed to a support on which the adjustable cell assembly is mounted and a ball nut mounted on the rod and secured to the housing.

3. A chromatography column as claimed in claim 2 in which each rod has fixed to it a gear wheel, the gear wheels of all the rods being interconnected by a ring gear.

4. A chromatography column as claimed in claim 3 in which


the gear wheels are disposed at the outside of the ring gear.


5. A chromatography column as claimed in any one of claims 2 to 4 including a handwheel fixed to a rod.

6. A chromatography column as claimed in any preceding claim including a brake for releasably holding the support assembly against adjustment by the drive means.

7. A chromatography column as claimed in claim 7 as dependent on any claim 3 in which the brake is a non-rotatable gear wheel movable into and out of engagement with a gear wheel of one of the rods.

8. A chromatography column having a support assembly substantially as hereinbefore described, or as shown in, Figures 2 to 4 of the accompanying drawings.









Fig 3

Fig 4

INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 99/01284

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 B01D15/08 G01N30/60

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 G01N B01D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 4 797 209 A (D.H.A. JACKSON) 10 January 1989 (1989-01-10) column 4, line 31 - line 37; figure 1 ----	1,2,8
A	EP 0 008 921 A (WRIGHT SCIENTIFIC LIMITED) 19 March 1980 (1980-03-19) ----	
A	US 5 324 426 A (T. JOSEPH) 28 June 1994 (1994-06-28) ----	
A	US 5 213 683 A (W.H.MANN) 25 May 1993 (1993-05-25) -----	



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "&" document member of the same patent family

Date of the actual completion of the international search

26 July 1999

Date of mailing of the international search report

16/08/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Hilgenga, K

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 99/01284

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
US 4797209	A	10-01-1989	JP	1199156 A	10-08-1989
EP 8921	A	19-03-1980	AU	5038379 A	13-03-1980
			JP	55039094 A	18-03-1980
US 5324426	A	28-06-1994	NONE		
US 5213683	A	25-05-1993	FR	2680115 A	12-02-1993
			GB	2258415 A, B	10-02-1993
			US	5282973 A	01-02-1994